

## BS-505/WP TELEPHONE SIREN WITH BEACON 230V AC



### TECHNICAL CHARACTERISTICS

OPERATION VOLTAGE	220-240V AC/50-60Hz
MAXIMUM POWER CONSUMPTION	4,5 VA
SOUND OUTPUT (1m)	105 dB (adjustable)
DEGREES OF COVER PROTECTION	IP 65
PRODUCED IN ACCORDANCE WITH	EN 50082-1, EN 61000-3-2, EN 61000-3-3
OPERATION TEMPERATURE RANGE	0 to 50 °C
RELATIVE HUMIDITY	Up to 95%
CONSTRUCTION MATERIALS	ABS-polycarbonate
EXTERNAL DIMENSIONS	140 x 137 x 90 mm
TYPICAL WEIGHT	320gr.
GUARANTEE	2 years

### GENERAL

The device BS-505/WP is connected to the telephone line in parallel with the telephone. It gives a strong sound output and a light signal during an incoming telephone call.

It is used in places with noisy environments, when an incoming telephone call (from a common telephone device) is impossible to be heard (i.e. Factories, laboratories, pubs, taxi stations e.t.c.

### INSTALLATION INSTRUCTIONS

1. Place a flat blade screwdriver to the 3 plastic hooks reception, to open the plastic cover
2. Pass the wires through the caps after making a small hall in the center of its cap and connect the siren

according to the schematic (*the ground connection is important*).

3. Install the plastic base using the included mounting accessories after placing the o-rings to the mounting screws. The siren should be mounted at a height of 2 - 3 metres from the floor, indoor or in covered outdoor spot.

4. Adjust the desirable siren's volume with the respective **volume** adjuster.

5. Place the sealing gaskets and refit with care the plastic cover in order to mount properly the plastic hooks and the siren is ready to operate.

