



ANTI-EXPLOSIVE
LED LIGHT



NEW EXPLOSION PROOF EMERGENCY LUMINARIES

▼ Designed for installation
in explosive atmospheres



Polycarbonate



Glass



Ex db IIC T6 Gb
Ex tb IIIC T85 Db

The company is certified by:

APPROVAL
SWISS
Objectively True

ISO 14001, OHSAS 18001, ISO 90001

40 years
Celebrating
1979-2019



**olympia™
electronics**
SAFETY & SECURITY SYSTEMS

for a safer world!

www.olympia-electronics.gr



**European
manufacturer**



OlympiaElectronics
International



olympiaelectronics
@olympiaelectro



Olympia Electronics



OlympiaElectronics



LED EMERGENCY LUMINARIES, SELF-TESTING, NON-MAINTAINED / POLYCARBONATE DIFFUSER

Type	Code	Battery	Consumption	Duration	Light Output (Mains / Emergency)	Gross weight	Dimensions
PTD1700XP	923411701	6V/1,6Ah	< 130mA	1 h	2100/750lm	4.600 gr.	485x375mm

LED EMERGENCY LUMINARIES, SELF-TESTING, MAINTAINED / NON-MAINTAINED / POLYCARBONATE DIFFUSER

Type	Code	Battery	Consumption	Duration	Light Output (Mains / Emergency)	Gross weight	Dimensions
PTD2700XP	923412703	6V/1,6Ah	< 190mA	1 h	4600/750lm	5.900 gr.	750x640mm
PTD2700XP3	923412707	6V/4Ah	< 200mA	3 h	4600/750lm	6.300 gr.	750x640mm

LED EMERGENCY LUMINARIES, SELF-TESTING, NON-MAINTAINED / 5mm GLASS

Type	Code	Battery	Consumption	Duration	Light Output (Mains / Emergency)	Gross weight	Dimensions
GTD1700XP	923411703	6V/1,6Ah	< 130mA	1 h	2400/800lm	5.400 gr.	485x375mm

LED EMERGENCY LUMINARIES, SELF-TESTING, MAINTAINED / NON-MAINTAINED / 5mm GLASS

Type	Code	Battery	Consumption	Duration	Light Output (Mains / Emergency)	Gross weight	Dimensions
GTD2700XP	923412711	6V/1,6Ah	< 190mA	1 h	4800/800lm	6.600 gr.	750x640mm
GTD2700XP3	923412715	6V/4Ah	< 200mA	3 h	4800/800lm	7.000 gr.	750x640mm

LED EMERGENCY LUMINARIES, SELF-TESTING, NON-MAINTAINED / POLYCARBONATE DIFFUSER

Type	Code	Battery	Consumption	Duration	Light Output	Gross weight	Dimensions
PTD1400X	923411401	3,6V/1,6Ah	< 25mA	1 h	350lm	4.745 gr.	485x375mm
PTD2700X	923412701	6V/1,6Ah	< 25mA	1 h	750lm	5.800 gr.	750x640mm
PTD1400X3	923411403	3,6V/4Ah	< 30mA	3 h	350lm	4.700 gr.	485x375mm
PTD2700X3	923412705	6V/4Ah	< 35mA	3 h	750lm	6.200 gr.	750x640mm

LED EMERGENCY LUMINARIES, SELF-TESTING, NON-MAINTAINED / 5mm GLASS

Type	Code	Battery	Consumption	Duration	Light Output	Gross weight	Dimensions
GTD1400X	923411405	3,6V/1,6Ah	< 25mA	1 h	400lm	5.300 gr.	485x375mm
GTD2700X	923412709	6V/1,6Ah	< 25mA	1 h	800lm	6.500 gr.	750x640mm
GTD1400X3	923411407	3,6V/4Ah	< 30mA	3 h	400lm	5.500 gr.	485x375mm
GTD2700X3	923412713	6V/4Ah	< 35mA	3 h	800lm	6.900 gr.	750x640mm

LED EMERGENCY LUMINARIES, CBS 230V AC / POLYCARBONATE DIFFUSER

Type	Code	Battery	Consumption	Duration	Light Output	Gross weight	Dimensions
PSL1100	923411100	-	< 65mA	-	1200lm	4.300 gr.	485x375mm
PSL1200	923411200	-	< 100mA	-	2200lm	4.400 gr.	485x375mm
PSL2200	923412200	-	< 100mA	-	2500lm	5.500 gr.	750x640mm
PSL2400	923412400	-	< 180mA	-	4200lm	5.600 gr.	750x640mm
PSL3400	923413400	-	< 180mA	-	4900lm	10.300 gr.	1360x1250mm

ACCESSORIES INCLUDED IN PACKAGE

Type	Code	Description	Gross weight
NPT34	751500102	Sealing grommet	105.5 gr.
A-FSA	808700069	Mounting base	156.5 gr.



The company is certified by:



Distributor



F-001-032

European
manufacturer

